



## SPECIFICATIONS

<b>General</b>	PIM Shield Cable Support Bars provide a low passive intermodulation mounting system to secure multiple Hybrid Snap-ins (sold separately) in high risk PIM zones. The Pole Mount Kit includes one Cable Support Bar plus all hardware required to secure the bar to a pole. An Extra Bar Kit can be added (sold separately) to double the number of connection points.
<b>Grip range</b>	2.37-inch to 4.5-inch OD pipe (2-inch to 4-inch nominal pipe)
<b>Snap-In mounting holes</b>	13 x 0.75-inch diameter
<b>Bar dimensions</b>	19.0-inch x 3.9-inch x 0.14-inch thick
<b>Hardware size</b>	½-13 UNC
<b>System PIM performance</b>	IM3 <-100 dBm when tested in accordance with proposed IEC 62037-8, near field test, 2x 20W test tones, while subjected to dynamic stimulus. To achieve specified PIM performance, torque hardware to 20 FT-LB (ConcealFab tool 900413)
<b>Material</b>	Galvanized Steel
<b>Operating temperature</b>	-40°C to +70°C
<b>Case dimensions</b>	8-inch x 4.5-inch x 20-inch
<b>Case weight</b>	31.1 lb.
<b>Qty per Case</b>	5