

EFT 500N5 SERIES

ELECTRICAL FAST TRANSIENT GENERATOR



FOR TESTS ACCORDING TO ...

- > ANSI/IEEE C62.41
- > EN 61000-4-4
- > EN 61000-6-1
- > EN 61000-6-2
- > IEC 60601-1-2
- > IEC 61000-4-4
- > IEC 61326
- > IEC 61850-3

EFT 500N5 SERIES - EFT/BURST TESTER

The EFT 500N5 series are the state-of-the-art EFT/Burst testers with a built-in coupling/decoupling network for single phase or three-phase mains supply lines and a HV terminal to connect a capacitive coupling clamp.







The spike frequency can be varied from as low as 100Hz up to 1,000kHz. The EFT 500N5 is capable to generate 10,000 spikes per second or up to 1,000 spikes per burst.

Its performance fully complies with IEC 61000-4-4 Ed.3:2012. Pre-programmed Standard Test routines and a number of selected User Test routines make the EFT 500N5 an optimum standalone solution for both testing during development and final testing of products and sub-assemblies.

HIGHLIGHTS

- > **10,000 pulses/sec.**
- > **4.8kV Burst voltage**
- > **Spike frequency up to 1MHz**
- > **Built-in 1ph or 3ph coupler up to 50A**
- > **Pulse verification acc. to Ed.3 on each coupling path**

APPLICATION AREAS

- | | |
|-------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|
|  INDUSTRY |  TELECOM |
|  MEDICAL |  COMPONENTS |
|  BROADCAST | |
|  RESIDENTIAL | |

TECHNICAL DETAILS

TECHNICAL DATA

EFT 500N5 MODELS

EFT 500N5.1	With 3-ph coupler, AC: 3x 440V/ 32A, DC: 270V/ 32A
EFT 500N5.2	With 3-ph coupler, AC: 3x 440V/ 50A, DC: 270V/ 50A
EFT 500N5.5	With 1-ph coupler, AC: 250V/ 32A, DC: 270V/ 32A
EFT 500N5.8	With 3-ph coupler, AC: 3x 690V/ 32A, DC: 270V/ 32A
Other couplers on request	

TEST LEVEL

Voltage range	200V - 4,800V
Into 50ohm	100V - 2,400V
Pulse shape	Into 50ohm load
Rise time tr	5ns ± 30%
Pulse width td	50ns ± 30%
Pulse shape	Into 1,000ohm load
Rise time tr	5ns ± 30%
Pulse width td	35ns to 150ns
Source impedance	50 Ohm ± 20%
Polarity	Positive/negative

TRIGGER

Release of Burst	Automatic, manual, external
Burst duration	Td = 0.10ms - 999.9ms
Burst repetition rate	Tr = 10ms - 9,999ms
Spike frequency	f = 0.1kHz - 1,000kHz
Test duration	T = 0:01 min - 99:59 min T > 99:59 min - endless

TECHNICAL DATA

OUTPUT

Direct	Via HV coax connector
Coupler	L, N and PE, all combinations
DUT supply AC 50/60Hz	single phase: 250V/ 32A, three-phases: 3x440V/ 32A or 50A,
DUT supply DC	270V/ 32A or 50A
DUT supply	Other DUT supply voltages on request
CRO Trigger	15V trigger signal for oscilloscope; burst duration and pulse frequency can be checked

TEST ROUTINES

Quick Start	Immediate start; easy to use and fast
User Test routines	Custom made test routine Change voltage after T Change frequency after T Frequency sweep within a burst Change burst duration after T Random release of bursts Synchronous burst mode Change polarity after T
Standard Test routines	As per IEC 61000-4-4, Automatic test Level X - Y
Service	Service, set-up, self test

INTERFACES

Serial interface	USB
Parallel interface	IEEE 488, address 1 - 30
CN interface	To control external CNI 503

GENERAL DATA

GENERAL DATA

Dimensions, weight	EFT 500N5.1: 19"/6HU, 22kg EFT 500N5.2: 19"/6HU, 40kg EFT 500N5.5: 19"/3HU, 20kg EFT 500N5.8: 19"/3HU, 23kg
Supply voltage	115/230V, +10/-15%
Fuses	2x 2 AT (230V), 2x 4 AT (115V)

TECHNICAL DETAILS

ENVIRONMENT	
Temperature	10 °C to 35 °C
Humidity	25 % to 75 %, non condensing
Atmospheric pressure	86 kPa (860 mbar) to 106 kPa (1 060 mbar)

OPTIONS

OPTIONS	
HFK	Coupling Clamp as per IEC 61000-4-4
KW 50	50ohm matching resistor for verification
KW 1000	1,000ohm matching resistor for verification
CA EFT kit	Kit for burst pulse verification consisting of KW50, KW1000 and adapter for DUT port with plastic case for storage
CA HFK kit	Adapter set for capacitive coupling clamp calibration included: - Transducer plate as per IEC/EN 61000-4-4 Ed 3.0 - Support for positioning the KW 50 adapter on 100mm height as the capacitive coupling clamp
A6dB	6dB attenuator
CNI 503	Coupling/decoupling networks, 3x440V/ 32A-63A-100A
iec.control	Software to control the test, including standard library, test report facility and data conversion generator

COMPETENCE WHEREVER YOU ARE



CONTACT EM TEST DIRECTLY

Switzerland

AMETEK CTS GmbH › Sternenhofstraße 15 › 4153 Reinach › Switzerland
Phone +41 (0)61 204 41 11 › Fax +41 (0)61 204 41 00
Internet: www.ametek-cts.com › E-mail: sales.conducted.cts@ametek.com

Germany

AMETEK CTS Europe GmbH › Customer Care Center EMEA › Lünener Straße 211
› 59174 Kamen › Germany
Phone +49 (0) 2307 26070-0 › Fax +49 (0) 2307 17050
Internet: www.ametek-cts.com › E-mail: info.cts.de@ametek.com

Poland

AMETEK CTS Europe GmbH › Biuro w Polsce › ul. Twarda 44 › 00-831 Warsaw › Poland
Phone +48 (0) 518 643 12
Internet: www.ametek-cts.com › E-mail: Infopolska.cts@ametek.com

USA / Canada

AMETEK CTS US › 52 Mayfield Ave › Edison › NJ 08837 › USA
Phone +1 732 417 0501
Internet: www.ametek-cts.com › E-mail: usasales.cts@ametek.com

P.R. China

AMETEK Commercial Enterprise (Shanghai) Co. Ltd. › Beijing Branch › Western Section, 2nd floor › Jing Dong Fang Building (B10) › Chaoyang District › Beijing, China, 100015
Phone +86 10 8526 2111 › Fax +86 (0)10 82 67 62 38
Internet: www.ametek-cts.com › E-mail: chinasales@ametek.com

Republic of Korea

EM TEST Korea Limited › #405 › WooYeon Plaza › #986-8 › YoungDeok-dong › Giheung-gu › Yongin-si › Gyeonggi-do › Korea
Phone +82 (31) 216 8616 › Fax +82 (31) 216 8616
Internet: www.emtest.co.kr › E-mail: sales@emtest.co.kr

Singapore

AMETEK Singapore Pte. Ltd › No. 43 Changi South Avenue 2 › 04-01 Singapore 48164
Internet: www.ametek-cts.com › E-mail: singaporesales.cts@ametek.com

Great Britain

AMETEK GB › 5 Ashville Way › Molly Millars Lane › Wokingham › Berkshire RG41 2 PL › Great Britain
Phone +44 845 074 0660
Internet: www.ametek-cts.com

Information about scope of delivery, visual design and technical data correspond with the state of development at time of release. Subject to change without further notice.