

# 1 GHz and 500 MHz High Voltage Differential Probes

## TDP1000, TDP0500, P6251 Datasheet



The TDP1000, TDP0500, and P6251 High-voltage Differential Probes provide excellent high-speed electrical and mechanical performance required for today's Switch Mode Power Supply (SMPS), CAN/LIN Bus, and high-speed digital system designs.

### Key performance specifications

- 1 GHz and 500 MHz probe bandwidth
- <1 pF differential input capacitance
- 1 MΩ differential input resistance
- ±42 v (DC + pk AC) differential input voltage
- >18 dB CMRR (at 250 MHz 50X attenuation)

### Key features

- Outstanding electrical performance
  - Selectable bandwidth-limiting filters
  - DC reject
- Versatile DUT connectivity
  - Small compact probe head for probing small geometry circuit elements
  - Straight pin, square pin, solder down, variable pitch standard accessories
  - Robust design for reliability

- Easy to use
  - Provides automatic units scaling and readout on the oscilloscope display
  - TDP1000, TDP0500
    - Connect directly to oscilloscopes with the TekVPI™ probe interface
    - Easy access to scope-displayed probe menu for probe setup control and operating status information
    - Remote GPIB/USB probe control through the oscilloscope
    - AutoZero – zeros out output offset
  - P6251
    - Connect directly to the TekProbe™ interface oscilloscopes, or to TekConnect® oscilloscopes using TCA-BNC adapter

### Applications

- High-speed switch mode power supply design
- CAN/LIN bus design
- Digital design and characterization
- Manufacturing engineering test
- Research and development

### High-voltage differential probes

The TDP1000, TDP0500, and P6251 High-voltage Differential Probes are specifically designed for use with and direct connection to Tektronix oscilloscopes with either the TekVPI™ probe interface, or TekProbe BNC Interface. These probes achieve high-speed signal acquisition and measurement fidelity by solving three traditional measurement challenges:

- Outstanding Electrical Performance
- Versatile Device-Under-Test Connectivity
- Ease of Use

## Specifications

All specifications are guaranteed unless noted otherwise. All specifications apply to all models unless noted otherwise.

### Warranted characteristics

<b>Bandwidth (probe only)</b>	
TDP1000, P6251	1 GHz
TDP0500	500 MHz
<b>Attenuation</b>	
	5X, 50X
<b>Differential mode input voltage</b>	
	$\pm 42$ v (DC + pk AC); $30 V_{rms}$
<b>Rise time (probe only)</b>	
TDP1000, P6251	$\leq 350$ ps
TDP0500	$< 700$ ps
<b>CMRR</b>	
	$> 55$ dB at 30 kHz
	$> 50$ dB at 1 MHz
	$> 18$ dB at 250 MHz (warranted at 50X attenuation)
<b>Max input voltage (nondestruct)</b>	
	$\pm 100$ V (DC + pk AC)
<b>Gain accuracy at DC</b>	
	$\pm 2\%$

### Typical characteristics

<b>Differential input capacitance</b>	
	$\leq 1$ pF
<b>Differential input resistance</b>	
	1 M $\Omega$
<b>Sensitivity/noise level</b>	
<b>5X attenuation</b>	2 mV <sub>rms</sub>
	10 mV <sub>rms</sub> (referred to the probe output)
<b>50X attenuation</b>	1 mV <sub>rms</sub>
	50 mV <sub>rms</sub> (referred to the probe output)
<b>Propogation delay</b>	
	6.5 ns
<b>Common mode input voltage</b>	
	$\pm 35$ v (DC + pk AC); $25 V_{rms}$
<b>Differential input offset range</b>	
TDP1000, TDP0500	$\pm 42$ V (5X or 50X attenuation)
P6251	$\pm 4.25$ V (5X attenuation)
	$\pm 42$ V (50X attenuation)
<b>DC reject</b>	
<b>5X attenuation</b>	0.4 Hz
<b>50X attenuation</b>	4 Hz

## Nominal characteristics

### Selectable bandwidth filter limits

TDP1000, TDP0500	100 Hz, 10 kHz, 1 MHz, Full
P6251	5 MHz, Full

### Oscilloscope interface recommendations

TDP1000, TDP0500	TekVPI™ Probe <sup>1</sup>
P6251	TekProbe BNC Level II TekConnect® (TCA-BNC required)

## Power requirements

TDP1000, TDP0500	Powered directly by oscilloscopes with the TekVPI interface
P6251	Powered directly by the TekProbe-BNC interface, eliminating the need for additional power supplies and cables when used with TekProbe-BNC oscilloscopes. May also be powered through the 1103 TEKPROBE power supply for use with non-TekProbe interface instrumentation.

## Physical characteristics

### Compensation box dimensions

Dimension	TDP1000, TDP0500		P6251	
	in	cm	in	cm
Height	1.6	4.1	1.0	2.6
Width	1.2	3.05	1.6	4.1
Length	4.2	10.7	3.2	8.13
Cable length	47.2 (inches), 1.2 (meters)			

### Weight

TDP1000, TDP0500		P6251	
lb	kg	lb	kg
0.320	0.146	0.360	0.163

<sup>1</sup> When using MSO/DPO2000/B series, the TekVPI Power supply (Tektronix part number, 119-7465-xx) and power cable is needed.

## Ordering information

### Models

TDP1000	1 GHz high-voltage differential probe with TekVPI interface.
TDP0500	500 MHz high-voltage differential probe with TekVPI interface.
P6251	1 GHz High-voltage Differential Probe with TekProbe-BNC Level II Interface.

### Options

#### Language options

Opt. L5	Japanese manual
Opt. L7	Simplified Chinese manual

#### Service options

Opt. C3	Calibration Service 3 Years
Opt. C5	Calibration Service 5 Years
Opt. R3	Repair Service 3 Years (including warranty)
Opt. R5	Repair Service 5 Years (including warranty)
Opt. SILV600	Standard warranty extended to 5 years
Opt. SILV900	Standard warranty extended to 5 years

#### Additional service products for the TDP0500 or TDP1000

TDP0500-R3DW / TDP1000-R3DW	Repair service coverage 3 years (includes product warranty period) 3-year period starts at time of customer instrument purchase
TDP0500-R5DW / TDP1000-R5DW	Repair service coverage 5 years (includes product warranty period) 5-year period starts at time of customer instrument purchase

### Accessories

#### Standard accessories

Description	Quantity included with product	Reorder part number (qty in reorder)
Y-lead set	2 each	196-3434-xx (1)
Solder-down lead set, 1 inch	1 each	196-3504-xx (1)
Solder-down lead set, 3 inch	1 each	196-3505-xx (1)
Micro CKT test tip	3 each	206-0569-xx (1)
Tip savers	2 each	016-1781-xx (2)
Longhorn adapters	2 each	016-1780-xx (5)
Straight-pin probe tips	8 each	016-1891-xx (8)
3-inch ground leads	2 each	196-3437-10 (2)
Color-coding bands	2 each of 5 colors	016-1315-xx (2 each of 5 colors)
Nylon carrying case	1 each	016-1952-xx (1)

**Standard warranty**

1 year parts and labor.

**Recommended accessories**

Description	Part number	Quantity
BNC to probe tip adapter	067-1734-xx	1 each
Spring loaded grounds	016-1782-xx	1 package of 6
Twin foot adapter	016-1785-xx	1 package of 4
Twin tip adapter	016-1786-xx	1 package of 4
IC micro grabber	SMK4	1 package of 4
TEKPROBE probe power supply	1103	1 each



Tektronix is registered to ISO 9001 and ISO 14001 by SRI Quality System Registrar.



Product(s) complies with IEEE Standard 488.1-1987, RS-232-C, and with Tektronix Standard Codes and Formats.

**ASEAN / Australasia** (65) 6356 3900  
**Belgium** 00800 2255 4835\*  
**Central East Europe and the Baltics** +41 52 675 3777  
**Finland** +41 52 675 3777  
**Hong Kong** 400 820 5835  
**Japan** 81 (3) 6714 3086  
**Middle East, Asia, and North Africa** +41 52 675 3777  
**People's Republic of China** 400 820 5835  
**Republic of Korea** +822 6917 5084, 822 6917 5080  
**Spain** 00800 2255 4835\*  
**Taiwan** 886 (2) 2656 6688

**Austria** 00800 2255 4835\*  
**Brazil** +55 (11) 3759 7627  
**Central Europe & Greece** +41 52 675 3777  
**France** 00800 2255 4835\*  
**India** 000 800 650 1835  
**Luxembourg** +41 52 675 3777  
**The Netherlands** 00800 2255 4835\*  
**Poland** +41 52 675 3777  
**Russia & CIS** +7 (495) 6647564  
**Sweden** 00800 2255 4835\*  
**United Kingdom & Ireland** 00800 2255 4835\*

**Balkans, Israel, South Africa and other ISE Countries** +41 52 675 3777  
**Canada** 1 800 833 9200  
**Denmark** +45 80 88 1401  
**Germany** 00800 2255 4835\*  
**Italy** 00800 2255 4835\*  
**Mexico, Central/South America & Caribbean** 52 (55) 56 04 50 90  
**Norway** 800 16098  
**Portugal** 80 08 12370  
**South Africa** +41 52 675 3777  
**Switzerland** 00800 2255 4835\*  
**USA** 1 800 833 9200

\* European toll-free number. If not accessible, call: +41 52 675 3777

**For Further Information.** Tektronix maintains a comprehensive, constantly expanding collection of application notes, technical briefs and other resources to help engineers working on the cutting edge of technology. Please visit [www.tek.com](http://www.tek.com).

Copyright © Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.

